



**NOTE:** INLET/OUTLET PVC PIPING TO BE SUPPLIED BY CUSTOMER

**SECTION A-A**

**GENERAL NOTES:**

- DESIGN SPECIFICATIONS CONFORM TO ALL STATE AND LOCAL PLUMBING CODES.
- 4500 PSI CONCRETE AT 28 DAYS
- ASTM A615, GRADE 60 REINFORCING
- HS 20 LOADING

**REINFORCEMENT (SLAB TOP)**

- #4 BARS @ PERIMETER OF THRU HOLE
- #4 BARS @ 6" O.C.E.W.

**REINFORCEMENT (BOTTOM SECTION)**

- #4 BARS @ 12" O.C.E.W. WALLS & FLOOR

Gals.	Grease Lbs.	Weight	Flow Rate GPM	
			Avg	Peak
1000	2,500	16,460	7.3	18.3

Inlet/Outlet	4"	6"
I	49"	47 1/2"
O	46"	44 1/2"



9235 Main Street #1  
 P.O. Box 507  
 Needville, Texas, 77461  
 1-888-331-5871

"Providing Concrete Environmental Solutions"

**GREASE INTERCEPTER  
 1000 GAL  
 (HEAVY DUTY)**

NC-005-007

Scale: 1/4" = 1'-0"  
 \* All Dimensions subject to allowable specification tolerances.

Date: 06/10/18

Approved By: \_\_\_\_\_ Date: \_\_\_\_\_